



Bilan

WRAPPER

BILAN suspended tapers are the best choice for perfect packaging of fodder balls in record time. Its use is very simple and reliable, a machine suitable for individuals or contractors working for third parties..





The final cut of the plastic is automatic, the telescopic blade gives us a perfect cut of the plastic, apart from this the grip without the plastic coming loose or escaping is very reliable, this ensures that we do not have to get off the tractor.
The plastic cutting is automatic, selectable according to the number of turns needed from the electronic box. .

We also have auxiliary switches on the machine itself to be able to open or close the blade manually when we are off the tractor.



BILAN wrapping machines include a ball dumper as standard. cancelable automatic, two plastic spool holder supports with auxiliary opening/closing control of the blade and the lower support roller.

The machine is prepared for balls from 1.20 to 1.50 m. Have display of the number of instant turns and the number of balls laminated.

There is the possibility of lengthening the taping process regardless of the number of turns selected, just by pressing a button.

The taping arm has an automatic stop device in case of trapping or hitting something and a hydraulic brake to completely block the arms.



CHARACTERISTICS	MODELS	
	PJ1A	
Nº. of taping arms	1	
70% plastic stretcher	serial	
50% plastic stretcher	serial	
Plastic breakage sensors	No	
Plastic coil height (mm)	750	
Single-Double replacement plastic coil support	Simple/2	
Drive lower rollers	serial	
Grooved drive rollers	Mixed	
Option 2 drive rollers with grooves	Optional	
Automatic roller inverter	serial	
Movement control box for the cabin	serial	
Automatic taping cycle with selection of number of turns of the arms	serial	
Auxiliary control of the plastic cutting blade on the frame	serial	
Lower support roller	serial	
Bypassable automatic ball dumper	serial	
Hydraulic brake on the wrapping arm	serial	
Minimum required tractor power (Cv)	30/40	
Minimum required tractor weight (Kg +/-)	>3400	
Minimum required flow rate (L/min)	25L	
Maximum required flow rate (L/min)	45L	
Minimum pressure (Bar)	135	
Sensor line (factory)	Optional	
Tractor coupling: Cat II	Yes	
Weight in running order (Kg)	680	